

# Autofrettage to Counteract Coefficient of Thermal Expansion Mismatch in Cryogenic Pressurized Pipes with Metallic Liners



Autofrettage to Counteract Coefficient of Thermal Expansion Mismatch in Cryogenic Pressurized Pipes with Metallic Liners

NASA Technical Reports Server (NTRS), et al., Ed. Wen

Filesize: 5.66 MB

## Reviews

*Complete information for book fanatics. It normally does not cost excessive. I am very easily can get a satisfaction of reading a created publication.*

*(Mrs. Winifred Fritsch)*

## AUTOFRETTAGE TO COUNTERACT COEFFICIENT OF THERMAL EXPANSION MISMATCH IN CRYOGENIC PRESSURIZED PIPES WITH METALLIC LINERS

[DOWNLOAD](#)

To download **Autofrettage to Counteract Coefficient of Thermal Expansion Mismatch in Cryogenic Pressurized Pipes with Metallic Liners** PDF, make sure you follow the web link below and download the ebook or get access to other information which might be highly relevant to **AUTOFRETTAGE TO COUNTERACT COEFFICIENT OF THERMAL EXPANSION MISMATCH IN CRYOGENIC PRESSURIZED PIPES WITH METALLIC LINERS** book.

BiblioGov. Paperback. Book Condition: New. This item is printed on demand. Paperback. 42 pages. Dimensions: 9.7in. x 7.4in. x 0.1in. Composite feedlines with metal liners have the potential to reduce weightcost while providing the same level of permeation resistance and material compatibility of all-metal feedlines carrying cryogenic propellants in spacecraft. The major technical challenges are the large difference in Coefficient of Thermal Expansion between the liner and the composite, and the manufacturing method required to make a very thin liner with the required strength and dimensional tolerance. This study investigates the use of autofrettage (compressive preload) to counteract Coefficient of Thermal Expansion when pre-pressurization procedures cannot be used to solve this problem. Promising materials (aluminum 2219, Inconel 718, nickel, nickel alloy) and manufacturing techniques (chemical milling, electroplating) are evaluated to determine the best liner candidates. Robust, autofrettaged feedlines with a low Coefficient of Thermal Expansion liner (Inconel 718 or nickel alloy) are shown to successfully counteract mismatch at LOX temperature. A new concept, autofrettage by temperature, is introduced for high Coefficient of Thermal Expansion materials (aluminum and pure nickel) where pressure cannot be used to add compressive preload. This item ships from La Vergne, TN. Paperback.



[Read Autofrettage to Counteract Coefficient of Thermal Expansion Mismatch in Cryogenic Pressurized Pipes with Metallic Liners Online](#)  
[Download PDF Autofrettage to Counteract Coefficient of Thermal Expansion Mismatch in Cryogenic Pressurized Pipes with Metallic Liners](#)

## Other eBooks

---



### [PDF] Kindle Fire Tips And Tricks How To Unlock The True Power Inside Your Kindle Fire

Access the hyperlink under to download "Kindle Fire Tips And Tricks How To Unlock The True Power Inside Your Kindle Fire" file.

[Read Document »](#)

---



### [PDF] Yearbook Volume 15

Access the hyperlink under to download "Yearbook Volume 15" file.

[Read Document »](#)

---



### [PDF] When Santa Claus Prayed

Access the hyperlink under to download "When Santa Claus Prayed" file.

[Read Document »](#)

---



### [PDF] Just So Stories

Access the hyperlink under to download "Just So Stories" file.

[Read Document »](#)

---



### [PDF] Molly on the Shore, BFMS 1 Study score

Access the hyperlink under to download "Molly on the Shore, BFMS 1 Study score" file.

[Read Document »](#)

---



### [PDF] Memoirs of Robert Cary, Earl of Monmouth

Access the hyperlink under to download "Memoirs of Robert Cary, Earl of Monmouth" file.

[Read Document »](#)